


شهادة مطابقة للمنتجات الخاضعة للوائح



Certificate of conformity for regulated products



We (.....TUV RHEINLAND OF NORTH AMERICA, INC.....) office number (.....04944.....) are bearing full responsibility for the product described below is conforms to the conformity assessment procedure Conduct the relevant technical regulations and standards which mentioned during this certificate.

Certificate Number	39456-049-21-513120	Issue Date	19/08/2021	Expire Date	19/08/2022
Certificate Type	Certificate of conformity for regulated products	Commercial Registration No	1010688565		
Establishment Address					
Product and Manufacturer Data					
Model Name	IS-47	Trade Mark	REVITARE		
Product Name	REVITARE NANO				
Product Description	Water-based varnish to Protect surfaces with virucidal and bactericidal properties				



Country of origin	Brazil	 TECHNICAL BULLETIN <table border="1"> <tr> <td>Product</td><td>Revitare Nano</td><td>CODE IS-047</td></tr> <tr> <td>Description</td><td colspan="2">It is a water-based varnish to protect surfaces with anti-corrosion properties. anti-viral, bacterial, and fungal properties. Applied on oil paints, epoxy, latex, textures, graffiti, plaster, and other surfaces such as metal, plastics, and wood.</td></tr> <tr> <td>Color</td><td colspan="2">Its color is milky and transparent after applied.</td></tr> <tr> <td>Benefits</td><td colspan="2"> > Disables viruses and bacteria within 02 > Makes the environment aseptic > Anti-mold > Zero addition of preservatives > Nanotechnology > Repels water > Protects the surface > Zero addition of solvents </td></tr> </table>  NORMATIVE REFERENCES <table border="1"> <thead> <tr> <th>Classification</th><th>Type</th><th>Description</th><th>Function/Definition</th></tr> </thead> <tbody> <tr> <td>This product meets ABNT-NBR 11702</td><td>4.8.6</td><td>Finishing for hygienic environments</td><td>Provides protective finish and contamination by microorganisms in susceptible environments</td></tr> </tbody> </table> TECHNICAL INFORMATION <table border="1"> <tr> <td>Composition</td><td colspan="3">Water, acrylic/styrene copolymers, thickener, nanobiocide, waxes and surfactants dispersed in water.</td></tr> <tr> <td>Toxicity</td><td colspan="3">CSDS - Chemical Safety Data Sheet, attached.</td></tr> <tr> <td>Packages</td><td colspan="3">3.6L, 18L, 200L and up to 20 m2 per liter</td></tr> <tr> <td>Yield per coat</td><td colspan="3">1.01 +/- 0.04 g/cm³</td></tr> <tr> <td>Density</td><td colspan="3">7.0 +/- 0.5</td></tr> <tr> <td>pH (ASTM E70 method - pH standard test of aqueous solutions with glass electrode)</td><td colspan="3">12 months</td></tr> <tr> <td>Shelf life (unopened, unused packaging)</td><td colspan="3">12 months</td></tr> </table> APPLICATION DETAILS <table border="1"> <thead> <tr> <th>Dilution</th><th>Finish</th><th>Packaging/Yield</th><th>Environments</th><th>Coats and Drying</th></tr> </thead> <tbody> <tr> <td> - Paintbrush, Roller, Spray Gun, Airless Foam and Immersion; READY TO USE. - Revolver: Dilute up to 5% </td><td>Satin</td><td>3.6L: up to 72m²/coat 18L: up to 360m²/coat 200L: up to 4000m²/coat</td><td>Indoor and Outdoor</td><td>2 coats with 02 hour interval. Touch: 01 hour. Handling: 03 hours</td></tr> </tbody> </table> <table border="1"> <tr> <td>Tools</td><td>Brush, Wool Roll, Spray Gun, Spray Revolver, Foam, Immersion.</td><td>Final: 72 hours.</td></tr> </table> <table border="1"> <tr> <td>Application and Security Procedure</td><td> Use PPE: Breathable Protective Mask, Goggles and Glove without Talc. The application site must be free of dirt, oils, stains, and cracks. Application must be uninterrupted and uniform over the entire surface. Wait for the indicated interval to apply the 2nd coat. </td></tr> </table> PRECAUTIONS Keep the packaging closed while in operation (product sensitive to light). Keep out of reach of children and animals. Do not reuse the packaging. Store in a cool, covered, ventilated place and away from heat sources. Keep the environment ventilated during preparation, application and drying. Use PPE. In case of contact with skin and eyes, wash with running water for 15 minutes. If swallowed, induce vomiting. Take the packaging to an appointment with your doctor. This product is intended for all types of buildings, metals, wood, plastics, wallpapers, floors, ceilings, and air ducts. This unopened and dry product packaging is classified as NON-HAZARDOUS/NON-INERT WASTE according to NBR 10.004. For further information or questions, please refer to the product's MSDS. Use only neutral products in the process of cleaning the applied surface. Alkaline petroleum products can remove the film. Medical emergencies (24 hours), CEATOX (Toxicological Assistance Center) 08000-148-110 Transport must be carried out in such a way that the packaging is upright and covered. Ensure conditions so that the product does not tip over. Incocryl Industria e Comercio de Tintas LTDA - ME - Rua Jacinto Gonçalves, 254 - Jardim Sao Jorge - Sao Paulo - SP - Postal Code 05568-240 Chemical Responsible: Hermes Paulo de Amorim Filho - CRQ 4th Region 0442687 TB created on: 6/3/2020 Version: 00.002 Revision: October 2020 - No. 002	Product	Revitare Nano	CODE IS-047	Description	It is a water-based varnish to protect surfaces with anti-corrosion properties. anti-viral, bacterial, and fungal properties. Applied on oil paints, epoxy, latex, textures, graffiti, plaster, and other surfaces such as metal, plastics, and wood.		Color	Its color is milky and transparent after applied.		Benefits	> Disables viruses and bacteria within 02 > Makes the environment aseptic > Anti-mold > Zero addition of preservatives > Nanotechnology > Repels water > Protects the surface > Zero addition of solvents		Classification	Type	Description	Function/Definition	This product meets ABNT-NBR 11702	4.8.6	Finishing for hygienic environments	Provides protective finish and contamination by microorganisms in susceptible environments	Composition	Water, acrylic/styrene copolymers, thickener, nanobiocide, waxes and surfactants dispersed in water.			Toxicity	CSDS - Chemical Safety Data Sheet, attached.			Packages	3.6L, 18L, 200L and up to 20 m2 per liter			Yield per coat	1.01 +/- 0.04 g/cm³			Density	7.0 +/- 0.5			pH (ASTM E70 method - pH standard test of aqueous solutions with glass electrode)	12 months			Shelf life (unopened, unused packaging)	12 months			Dilution	Finish	Packaging/Yield	Environments	Coats and Drying	- Paintbrush, Roller, Spray Gun, Airless Foam and Immersion; READY TO USE. - Revolver: Dilute up to 5%	Satin	3.6L: up to 72m²/coat 18L: up to 360m²/coat 200L: up to 4000m²/coat	Indoor and Outdoor	2 coats with 02 hour interval. Touch: 01 hour. Handling: 03 hours	Tools	Brush, Wool Roll, Spray Gun, Spray Revolver, Foam, Immersion.	Final: 72 hours.	Application and Security Procedure	Use PPE: Breathable Protective Mask, Goggles and Glove without Talc. The application site must be free of dirt, oils, stains, and cracks. Application must be uninterrupted and uniform over the entire surface. Wait for the indicated interval to apply the 2nd coat.
Product	Revitare Nano	CODE IS-047																																																															
Description	It is a water-based varnish to protect surfaces with anti-corrosion properties. anti-viral, bacterial, and fungal properties. Applied on oil paints, epoxy, latex, textures, graffiti, plaster, and other surfaces such as metal, plastics, and wood.																																																																
Color	Its color is milky and transparent after applied.																																																																
Benefits	> Disables viruses and bacteria within 02 > Makes the environment aseptic > Anti-mold > Zero addition of preservatives > Nanotechnology > Repels water > Protects the surface > Zero addition of solvents																																																																
Classification	Type	Description	Function/Definition																																																														
This product meets ABNT-NBR 11702	4.8.6	Finishing for hygienic environments	Provides protective finish and contamination by microorganisms in susceptible environments																																																														
Composition	Water, acrylic/styrene copolymers, thickener, nanobiocide, waxes and surfactants dispersed in water.																																																																
Toxicity	CSDS - Chemical Safety Data Sheet, attached.																																																																
Packages	3.6L, 18L, 200L and up to 20 m2 per liter																																																																
Yield per coat	1.01 +/- 0.04 g/cm³																																																																
Density	7.0 +/- 0.5																																																																
pH (ASTM E70 method - pH standard test of aqueous solutions with glass electrode)	12 months																																																																
Shelf life (unopened, unused packaging)	12 months																																																																
Dilution	Finish	Packaging/Yield	Environments	Coats and Drying																																																													
- Paintbrush, Roller, Spray Gun, Airless Foam and Immersion; READY TO USE. - Revolver: Dilute up to 5%	Satin	3.6L: up to 72m²/coat 18L: up to 360m²/coat 200L: up to 4000m²/coat	Indoor and Outdoor	2 coats with 02 hour interval. Touch: 01 hour. Handling: 03 hours																																																													
Tools	Brush, Wool Roll, Spray Gun, Spray Revolver, Foam, Immersion.	Final: 72 hours.																																																															
Application and Security Procedure	Use PPE: Breathable Protective Mask, Goggles and Glove without Talc. The application site must be free of dirt, oils, stains, and cracks. Application must be uninterrupted and uniform over the entire surface. Wait for the indicated interval to apply the 2nd coat.																																																																
HS Code	320990900001																																																																
Technical Regulation	Technical regulation for Paints (Pigments) and Varnishes																																																																
Manufacturer name	INCOCRYL TINTAS E VERNIZES																																																																
Product test data																																																																	
Report number	107937																																																																
Report Date	17/08/2021																																																																
Decision of conformity assessment	Product Approved																																																																

CB Organization Office
Responsabile Manager
signature

19/08/2021 03:41

CB Organization Office
Stamp



تفاصيل

تفاصيل أرقام الموديلات

عودة (ContactOfficer/MyRequests/HRRequests/)

أحكام وشروط (Home/Terms/) | اتصل بنا (home/ContactUs/) | بوابة الهيئة (http://www.saso.gov.sa/ar/contactus/Pages/default.aspx)

تحت اشراف تطوير و تشغيل



الهيئة السعودية للمواصفات والمقاييس والجودة © 2021